

QUALITY PRINTING GUIDELINES

FONT SIZE (minimum): 6pt
Any smaller and it can become illegible

LINE THICKNESS (minimum): 0.5pt

Any smaller and it can blur or print thicker than expected

NEGATIVE SPACE THICKNESS (minimum): 0.7pt *the unprinted space in between printed areas

Any smaller and it will be filled in by the surrounding printed areas


NUMBER OF PRINT COLORS (maximum): 4 colors (per side) FROM THE PANTONE SOLID-COATED COLORBOOK

*Your account manager can provide you with a PDF of the colorbook upon request. 1 stock color 1 location included free. Ask your account manager regarding the cost of additional colors and custom color matching.

WARNING:
If you do not adhere to these print specifications your print may gap or fill-in during printing.



All type in your design must be AT LEAST this size





#2: xxx

#2: xxx

#3: xxx

#2: xxx

#3: xxx

#2: xxx

#3: xxx

#2: xxx

#3: xxx

PLEASE REVIEW YOUR PROOF TO APPROVE FOR PRINTING

Please review this proof for layout, spelling, punctuation, color selection and design approval. The colors shown are an approximation of the ink colors selected from the Pantone Solid-Coated Colorbook. The Pantone colors listed under the lighters on this proof will be the ones printed on your lighters. Please refer to a Pantone Guide to view actual colors.



#2: xxx

#3: xxx

#2: xxx

#3: xxx

#2: xxx

#3: xxx

#2: xxx

#3: xxx

#2: xxx

#3: xxx